

New Product Announcement | Series G 3000

Static Grounding Reels Series G 3000

Reelcraft's static discharge reels are used to ground equipment operating in hazardous areas. When properly clamped to the ground, the static discharge reel dissipates static electrical buildup, reducing the chances of sparking and the potential for explosion. The new GS3050 reel with a 304 stainless steel casing offers an added resistance to corrosion, heat and chemicals and is supplied with 50' of stainless steel cable.

Benefits

- **Strength** - Made from industrial grade carbon or stainless steel.
- **Compact design** - Reels require little mounting space for applications where space is a critical requirement.
- **Constant tension** - A turn of the nob changes reel from spring return to constant tension (spring driven models only).
- **Versatility** - Guide arm adjusts to one of several payout positions requiring only standard tools (GA3100 N and GHC3100 N only).

NEW!

Stainless steel
GS3050



Dual cables
G 3050 Y



Hand crank
GHC3100 N



		Size Index			
		1		2	
		in	mm	in	mm
A	8 ⁷ / ₈	224	9 ³ / ₄	248	
B	8 ⁵ / ₈	219	9 ¹ / ₄	235	
C	7 ⁷ / ₈	200	7 ⁷ / ₈	200	
D	1 ¹ / ₂	38	1 ¹ / ₈	29	
E	3 ³ / ₈	86	3 ³ / ₄	96	

		Size Index	
		3	
		in	mm
A	9 ¹ / ₄	235	
B	9 ³ / ₄	248	
C	5 ¹ / ₄	134	
D	7 ⁷ / ₈	200	
E	1 ¹ / ₈	29	

Model	Cable Extended		Clamp Rating	Max Temperature		Cable Notes	Shipping Weight		Size Index
	ft	m		°F	°C		lbs	kg	
Spring Driven Painted Carbon Steel Reels									
G 3050	50	15	100 AMP	150	66	Single 7 x 7 stranded steel*	12	5	1
G 3050 Y	50	15	100 AMP	150	66	35' (9.2m) plus dual 15' (4.6m) for Y* Total extension 50' (15m)	12	5	1
G 3050 N	50	15	100 AMP	150	66	Hi-vis orange nylon covered cable**	12	5	1
GA3100 N	100	30	100 AMP	125	52	Hi-vis orange nylon covered cable**	16	7	2
Hand Crank Painted Carbon Steel Reels									
GHC3100 N	100	30	100 AMP	125	52	Hi-vis orange nylon covered cable**	12	5	3
Spring Driven Stainless Steel Reels									
NEW! GS3050	50	15	100 AMP	150	66	Single 7 x 7 stranded stainless steel*	12	5	1

*3/32" OD steel aircraft cable. DC resistance is approximately one ohm per 50 ft. of steel cable. **Nylon covered cable (1/8" O.D.).

Models listed with an icon can ship same day upon request when the order is received by 1:00 PM Eastern Time for quantities of 10 or fewer.

Indiana Warehouse

Indiana & California

California Warehouse

Canadian Warehouse